

Colonne per stampi plastica tipo "PTR" con guida spallata

- Materiale: 16 Ni Cr 4
- Esecuzione: cementate, temprate, retificate
- Tolleranza: d g6
- Durezza: HRC 60/62


Colonne PTR
16 x 36 x 80
Est. 34 25 x 96 x 200

Cod.
1CO
1COPTR

Mat.
PTR
E34

Mis.
16036980
25096200

Made in Italy



d	d1	d2	k	l2	l1	l										
						70	80	100	120	140	160	180	200	220		
16	22	26	5	10	26	•	•	•	•	•						
					36	•	•	•	•	•						
					46		•	•	•	•	•					
					56			•	•	•	•	•				
					66			•	•	•	•	•	•			
					76				•	•	•	•	•	•		
20	30 28A	34 32A	6	10	36	•	•	•	•	•	•					
					46		•	•	•	•	•	•				
					56			•	•	•	•	•	•			
					66			•	•	•	•	•	•	•		
					76				•	•	•	•	•	•	•	
					96					•	•	•	•	•	•	
25	36 34A	40 38A	7	10	36		•	•	•	•	•	•				
					46			•	•	•	•	•	•			
					56			•	•	•	•	•	•	•		
					66			•	•	•	•	•	•	•		
					76				•	•	•	•	•	•		
					96					•	•	•	•	•		
32	40	45	7	10	36			•	•	•	•	•	•			
					46			•	•	•	•	•	•	•		
					56			•	•	•	•	•	•	•		
					66			•	•	•	•	•	•	•		
					76				•	•	•	•	•	•		
					96					•	•	•	•	•		
					106						•	•	•	•		
					116							•	•	•		
					126								•	•		
40	48	52	8	10	46			•	•	•	•	•	•			
					56			•	•	•	•	•	•			
					66			•	•	•	•	•	•			
					76				•	•	•	•	•			
					96					•	•	•	•			

A Specificare questo diametro esterno.